EEV Aluminium Electrolytic Capacitors

SMD Surface mount lead - Ultra Low Impedance 105℃ / 2000 h

Applications: AV, Computer/Monitor, Communications, SMPS
Features: Low Profile vertical chip, Ultra Low Impedance

ΦD	L	H	H1	A	B	C	P
4.0	5.4	5.5 MAX	4.3	0.65 ±0.1	1.8	0.35 +0.15,-0.20	1.0 ±0.2
5	5.4	6.5 MAX	5.3	0.65 ±0.1	2.2	0.35 +0.15,-0.20	1.5 ±0.2
6.3	5.4	7.8MAX	6.6	0.65 ±0.1	2.6	0.35 +0.15,-0.20	1.8 ±0.2
6.3	7.7	7.8 MAX	6.6	0.65 ±0.1	2.6	0.35 +0.15,-0.20	1.8 ±0.2
8	6.2	9.5 MAX	8.3	0.65 ±0.1	3.4	0.35 +0.15,-0.20	2.2 ±0.2
8	10.2	10.0 MAX	8.3	0.90 ±0.2	3.4	0.70 ±0.2	3.1 ±0.2
10	10.2	12.0 MAX	10.3	0.90 ±0.2	3.5	0.70 ±0.2	4.6 ±0.2



Electrical Characteristics

Rated Voltage	6.3 to 35Vdc
Operating Temperature	-40℃ to +105℃
Capacitance Range	4.7µF to 1500µF
Capacitance Tolerance	±20% at 120Hz / 20℃
Endurance Test	2000 hours (see conditions in Test method and performance)
Leakage Current	I≤0.01CV or 3µA which ever is greater after rated voltage has been applied for 2 minutes at 20℃

Multiplier for Ripple Current

Frequency (Hz)	120Hz	1KHz	10KHZ	100KHz
Coefficient	0.70	0.80	0.90	1.00

Capacitance (µF)	Rated Voltage (Surge Voltage) Vdc											
	6.3 (8)				10 (13)				16 (20)			
	ØD x L (mm)	tanδ 120Hz 20℃	RC (mA) 100KHz 105℃	Z (Ω) 100KHz 20℃	ØD x L (mm)	tanδ 120Hz 20℃	RC (mA) 100KHz 105℃	Z (Ω) 100KHz 20℃	ØD x L (mm)	tanδ 120Hz 20℃	RC (mA) 100KHz 105℃	Z (Ω) 100KHz 20℃
22	4x5.4	0.26	90	1.93	4x5.4	0.19	90	1.93	4x5.4	0.16	90	1.93
									5x5.4	0.16	160	1.00
33	4x5.4	0.26	90	1.93	4x5.4	0.19	90	1.93	5x5.4	0.16	160	1.00
					5x5.4	0.19	160	1.00				
47	4x5.4	0.26	90	1.93	6.3x5.4	0.19	190	0.52	5x5.4	0.16	160	1.00
	5x5.4	0.26	160	1.00					6.3x5.4	0.16	240	0.52
100	5x5.4	0.26	160	1.00	6.3x5.4	0.19	190	0.52	6.3x5.4	0.16	240	0.52
	6.3x5.4	0.26	240	0.52								
150	6.3x7.7	0.26	240	0.30	6.3x7.7	0.19	240	0.34	6.3x7.7	0.16	280	0.34
220	6.3x7.7	0.26	240	0.30	6.3x7.7	0.19	280	0.34	6.3x7.7	0.16	280	0.34
									8x10.2	0.16	370	0.22
330	6.3x7.7	0.26	280	0.34	8x10.2	0.19	600	0.16	8x10.2	0.16	600	0.16
	8x6.2	0.26	300	0.26								
470	8x10.2	0.26	600	0.16	8x10.2	0.19	600	0.16	8x10.2	0.16	600	0.16
680	8x10.2	0.26	600	0.16	10x10.2	0.19	600	0.12	10x10.2	0.16	850	0.08
1000	8x10.2	0.26	600	0.16	10x10.2	0.19	850	0.08				
1500	10x10.2	0.26	850	0.08								

Capacitance (µF)	Rated Voltage (Surge Voltage) Vdc							
	25 (32)				35 (44)			
	ØD x L (mm)	tanδ 120Hz 20℃	RC (mA) 100KHz 105℃	Z (Ω) 100KHz 20℃	ØD x L (mm)	tanδ 120Hz 20℃	RC (mA) 100KHz 105℃	Z (Ω) 100KHz 20℃
4.7					4x5.4	0.12	90	1.93
10	4x5.4	0.14	90	1.93	4x5.4	0.12	90	1.93
					5x5.4	0.12	160	1.00
22	5x5.4	0.14	160	1.00	5x5.4	0.12	160	1.00
33	5x5.4	0.14	160	1.00	6.3x5.4	0.12	240	0.52
	6.3x5.4	0.14	240	0.52				
47	6.3x5.4	0.14	240	0.52	6.3x5.4	0.12	240	0.52
68	6.3x5.4	0.14	240	0.52	6.3x7.7	0.12	280	0.34
100	6.3x7.7	0.14	280	0.34	6.3x7.7	0.12	280	0.34
					8x10.2	0.12	600	0.16
150	8x10.2	0.14	600	0.16	8x10.2	0.12	600	0.16
220	8x10.2	0.14	600	0.16	8x10.2	0.12	600	0.16
330	8x10.2	0.14	600	0.16	10x10.2	0.12	850	0.08
470	10x10.2	0.14	850	0.08				

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.